

TITLE 24 JA8 COMPLIANT

NOVA FLEX[®]



Approved by the state of California, Title 24 JA8 Compliant products have been tested to meet higher standards. JA8 applies to any residential construction project that requires a permit: single-family homes, multi-family homes up to three stories high, apartment units in residential high-rises, guest rooms in hotels and motels, and other niche applications.

Standard IP65 Design Series

NF/SP-DS-O-64-24V-2200K*
NF-DS-O-64-24V-2500K
NF-DS-O-64-24V-2700K
NF-DS-O-64-24V-3000K
NF-DS-O-64-24V-3500K
NF/SP-DS-O-128-24V-2200K*
NF-DS-O-128-24V-2500K
NF-DS-O-128-24V-2700K
NF-DS-O-128-24V-3000K
NF-DS-O-128-24V-3500K
NF/SP-DS-O-160-24V-2200K*
NF-DS-O-160-24V-2500K
NF-DS-O-160-24V-2700K
NF-DS-O-160-24V-3000K
NF-DS-O-160-24V-3500K
NF/SP-DS-O-240-24V-2200K*
NF-DS-O-240-24V-2500K
NF-DS-O-240-24V-2700K
NF-DS-O-240-24V-3000K
NF-DS-O-240-24V-3500K

Rugged IP68 Design Series

NF/SP-DS-W-64-24V-2200K*
NF-DS-W-64-24V-2500K*
NF-DS-W-64-24V-2700K*
NF-DS-W-64-24V-3000K
NF-DS-W-64-24V-3500K*
NF/SP-DS-W-128-24V-2200K*
NF-DS-W-128-24V-2500K*
NF-DS-W-128-24V-2700K*
NF-DS-W-128-24V-3000K
NF-DS-W-128-24V-3500K*
NF/SP-DS-W-160-24V-2200K*
NF-DS-W-160-24V-2500K*
NF-DS-W-160-24V-2700K*
NF-DS-W-160-24V-3000K
NF-DS-W-160-24V-3500K *
NF/SP-DS-W-240-24V-2200K*
NF-DS-W-240-24V-2500K*
NF-DS-W-240-24V-2700K*
NF-DS-W-240-24V-3000K
NF-DS-W-240-24V-3500K*

Note: Title 24 does not allow lights higher than 4000K | 90+ CRI is the minimum for the Standard.



Nova Flex LED is a UL System Certified Provider. All ribbon and neon is UL Certified and the facility undergoes regular inspection to ensure we deliver the highest quality customized solutions.