




# ANGLED 1919U CHANNEL

**NOVA** FLEX®



## Physical

Material	Anodized Aluminum
Length	2M**
Channel Options [Light Loss]	Silver [10%] Black [20%] White [0%]
Lens Options [Light Transmission]	Clear [92%] Soft [78%] Black [25%]

Lenses are suitable for outdoor use with respect to exposure to ultraviolet light and water exposure in accordance with UL 746C. Every 2M of channel comes with 4 mounting clips and 2 end caps, one with a hole and one solid.

## Product Codes for Ordering

Channel	Silver: NF-CH-1919U-2M Black: NF/SP-CH-1919U-2M-BK* White: NF/SP-CH-1919U-2M-WT*
Lens	Clear: NF-CH-1919U-C/CLEAR-2M Soft: NF-CH-1919U-C/SOFT-2M Black: NF/SP-CH-1919U-C/BLACK-2M*


## Mounting Options




Direct Mount



Mount with Clips  
NF-CH-1919U-CLIP



Adjustable Clip  
Angles: 0°/15°/30°/45°/60°/75°/90°  
NF-CH-UNV-CLIP/ADJ



## Dotting & Compatibility

LEDs	DS64	DS128	DS160	DS240	H2128	PRO60	PRO120	PRO240	ADJ160	RGB60	RGBW60	DRGB48
IP65	2	1	1	1	1	2	1	1	2	2	2	2

IP68 LED strips not compatible

0 - No Dotting



1 - Slight Dotting



2 - Blurred Dotting



3 - Clear Dotting

\*Special Order Product Notes:  
Lead-time 7-9 weeks  
MOQ 150 pcs (2M/pc)

FOR MORE  
INFORMATION  
CLICK HERE



PROJECT SUPPORT

INSTALL GUIDE

WHY NOVA FLEX