



- Amazing 360-degree LED neon light emits from entire silicone surface
 - Enables unique, truly “WOW” neon fixtures
- [See all configuration / fixture options in our selection guide](#)
 - Made to order, 7-9 week lead-time
- Five static white color temperature options
- Matte-finish to minimize dust, static
- CRI90+



THE COMPLETE ASSEMBLED SOLUTION

Project Name _____

Fixture Type _____

Phase _____

Specifier _____

Date _____

SKU _____

SKU _____

SKU _____

SKU _____

PERFORMANCE

SKU	L/ft	EFFICACY (L/W)	POWER (W/ft)	MAX RUN	LED/M
NF/SP-NEON-0-360-24V-2200K	233	53.0	4.4	16.4 ft	336
NF/SP-NEON-0-360-24V-2700K	251	57.2	4.4	16.4 ft	336
NF/SP-NEON-0-360-24V-3000K	257	58.5	4.4	16.4 ft	336
NF/SP-NEON-0-360-24V-4000K	250	56.9	4.4	16.4 ft	336
NF/SP-NEON-0-360-24V-5700K	277	63.0	4.4	16.4 ft	336

ELECTRICAL

Voltage	24V
Wire Size	20 AWG
Lead	8 in/200 mm
Dimming	See compatible controls on page 3


QUALITY ASSURANCE

CCT Binning	SDCM < 3
Warranty	5 years
Certifications	cULus, RoHS, CE
Lumen Maintenance	50,000 Hrs

PHYSICAL

Ambient Temp	13° to 120°F
Environment	INDOOR
Mounting	See Mounting Section
Diameter	.91 in
Cut Length	.47 in
Min. Bend Diameter	8.66 in
Max Run	Please see selection guide for related parameters for each 360 neon configuration

LIGHT DISTRIBUTION [3000K]



CRI/R9 | 3000K 98.2 / 91

Rf/Rg @ 3000K 95 / 101

Beam Angle

360°

DOWNLOAD FULL
PHOTOMETRIC DATA HERE

360 NEON DRIVER OPTIONS

	Product Image	Product Code	Wattage	Current/Voltage	Safety	Downloads
Universal Dim / Non-Dim		NF-PS-UNV-60W-24V Dim 0-10V, MLV, ELV TRIAC View spec sheet for all options	60W	Output Current: 2.5A Input Voltage: 100-277 VAC	UL8750 Class 2 Type HL FCC	SPEC SHEET
		NF-PS-UNV-96W-24V Dim 0-10V, MLV, ELV TRIAC View spec sheet for all options	96W	Output Current: 4A Input Voltage: 100-277 VAC	UL8750 Class 2 Type HL FCC	SPEC SHEET
		NF-PS-UNV-288W-24V Dim 0-10V, MLV, ELV TRIAC View spec sheet for all options	288W	Output Current: 3x4A Input Voltage: 100-277 VAC	UL8750 Class 2 Type HL FCC	SPEC SHEET
		NF-PS-UNV-384W-24V Dim 0-10V, MLV, ELV TRIAC View spec sheet for all options	384W	Output Current: 4x4A Input Voltage: 100-277 VAC	UL8750 Class 2 Type HL FCC	SPEC SHEET
0 - 10V Dim Only		NF-PS-MAXX-30W-24V-0/10V	30W	Output Current: 1.25A Input Voltage: 100-277 VAC	UL8750 Class 2 Type HL FCC	SPEC SHEET
		NF-PS-MAXX-288W-24V-0/10V	288W	Output Current: 20A Input Voltage: 100-277 VAC	UL 7850 UL1310	SPEC SHEET
		NF-PS-96W-24V-0/10V	96W	Output Current: 0.96A Max Input Voltage: 120-277 VAC	UL8750 Class 2	SPEC SHEET
Lutron		NF-PS-L3DA-40W-24V-KL Lutron Hi-Lume 1% EcoSystem/3-Wire 24V	40W	Output Current: 3.3A Input Voltage: 120-277 VAC	UL8750 Class 2 Type TL	SPEC SHEET
		NF-PS-L3DO-96W-24V Lutron Hi-Lume Premier 0.1% EcoSystem/3-Wire 24V Constant Voltage	96W	Output Current: 4.0A Input Voltage: 120-277VAC	UL8750 CSA250.13-14 Class 2	SPEC SHEET

	Product Image	Product Code	Details	Downloads
S3i Series		S3i Glass Touch-Panel NF-S3i-TP-D	Required to Pair: S3i-WR-1009 Zones: 4 Power Consumption: 200ma Dimming Function: 0 - 100%	SPEC SHEET
		S3i Hand-Held Remote NF-S3i-WC-D	Required to Pair: S3i-WR-1009 Zones: 6 Dimming Function: 0 - 100% Battery Operated: 3 AAA	SPEC SHEET
		S3i Push Button Wall Mount NF-S3i-PB-D	Required to Pair: S3i-WR-1009 Zones: 1 Dimming Function: 0 - 100% Battery Operated: 3V (CR2025)	SPEC SHEET
		S3i Wireless Receiver All controls above require this product NF-S3i-WR-1009	Output Power: 240 - 720w Output Current: 4 CH. 5A/CH Input: 12 - 36V DC Dimming: 0 - 100% Can pair with NF-A-UNV	SPEC SHEET
Amplifier		Universal Amplifier NF-A-UNV	Input Voltage: 12 - 36V DC Input Signal: PWM Max Load Current: 20A (5A/4CH) Max Output Power: 240 - 720W	SPEC SHEET

360 NEON ACCESSORY OPTIONS



Product Image	Product Code	Dimensions
	Hardwire to Female Quick Connect Adapter NF-C-F	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, & 10ft
	Hardwire to Male Quick Connect Adapter NF-C-M	Available Lengths: 6in, 1ft, 2ft, 3ft, 4ft, 5ft, 6ft, 8ft & 10ft
	Male to Female Quick Connect Adapter NF-C-MF	Available Lengths: 3ft, 6ft & 10ft
	Y Cable 2 Male, 1 Female NF-C-Y	Total Length: 20.00 in
	Y Cable 4 Male, 1 Female NF-C-Y-4Y	Total Length: 20.00 in
	Y Cable 8 Male, 1 Female NF-C-Y-8Y	Total Length: 17.25 in
	Female Quick Connect to Hardwire Adapter NF-C-F/HW	1.5 x 0.5 x 0.5 in
	Male Quick Connect to Hardwire Adapter NF-C-M/HW	1.5 x 0.5 x 0.5 in

FOR MORE
INFORMATION
CLICK HERE



RESOURCES

WHY NOVA FLEX

ADDITIONAL
PRODUCT OPTIONS