

COMPATIBILITY - CHANNEL

NFDS 2.4W | NF-DS-64



IP RATING

DMP DMP WET WET

BODY COLOR

SLV Silver BLK Black* WHT White*

LENS TYPE

CLR Clear SFT Soft BLK Black SLD Solid

SURFACE

1707

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK, SLD

Angles: 1707-30°, 1707-60°

3525

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

1813

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

RECESSED

2515

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

4540

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

ANGLED

1919U

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

3030 SQ **3030 CR**

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

BENDABLE

3916

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

1806

Options: DMP, WET, SLV, CLR, BLK, SFT, WHT, BLK

*Lead time for this configuration is 7-10 weeks

Nova Flex LED LLC retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Oct.20.23.06:30

800.595.6302

novaflexled.com

COMPATIBILITY - CHANNEL

NFDS 2.4W | NF-DS-64



IP RATING

DMP Damp **WET** Wet

BODY COLOR

SLV Silver **BLK** Black* **WHT** White*

LENS TYPE

CLR Clear **SFT** Soft **BLK** Black **SLD** Solid

UNIVERSAL

3560

Bottom
Middle
Top

2.36"

1.38"

DMP **WET**

SLV **BLK** **WHT**

CLR **SFT** **BLK**

2217

0.71"

0.89"

0.68"

DMP **WET**

SLV **BLK** **WHT**

CLR **SFT** **BLK**

MUD-IN

6214

2.42"

0.81"

1.12"

0.55"

DMP **WET**

SLV **BLK** **WHT**

CLR **SFT** **BLK**

CHANNELESS

2913

0.56"

0.51"

1.14"

DMP **WET**

SFT

SUSPENDED

3030 RN

0.83"

1.18"

1.18"

DMP **WET**

SLV **BLK** **WHT**

SFT

*Lead time for this configuration is 7-10 weeks

Nova Flex LED LLC retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Oct.20.23.06:30





800.595.6302

novaflexled.com

RESOURCE - CHANNEL LENS DOTTING

NFDS 2.4W | NF-DS-64



Dotting with soft lens		O - Damp	W - Wet	
Angled	1919U	2	x	0 - No Dotting 
	3030 SQ/CR	1	1	
Bendable	1806	3	x	1 - Slight Dotting 
	3916	1	1	
Mud-In	6214	1	2	2 - Blurred Dotting 
Recessed	2515	1	x	3 - Clear Dotting 
	4540	0	0	
	6017	1	1	
Universal	2217	1	2	X Not Compatible
	3560-B	1	1	
	3560-M	3	3	
Suspended	3030	0	1	
Surface	1707	3	x	
	1813	2	2	
	3525	0	0	
	4517	1	1	
Channel-less	2913	1	x	

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Oct.20.23.06:30

800.595.6302

novaflexled.com