


ORDER GUIDE - DESIGN SERIES STATIC COLOR

NFDS-STC 1.6W | NF-DS-60



PART NUMBER BUILDER:




Notes:

1 *IP68 is available with a lead time of 7-10 weeks

ENVIRONMENT AND DIMENSIONS

IN INCHES UNLESS NOTED



Section	Damp	Wet
A	0.40" (10.16 mm)	0.52" (13.21 mm)
B	3.93" (9.98 cm)	3.93" (9.98 cm)
C	0.65" (16.4 mm)	0.65" (16.4 mm)
D	0.14" (3.56 mm)	0.22" (5.59 mm)

ILLUMINATION DETAILS

CCT	Lumens/Ft	Efficacy (lm/w)	Power (w/ft)	Max Run
Red	43	27	1.6	48.8' Ft
Green	69	43		
Blue	16	9		
Yellow	32	20		

Lumens have a tolerance of +/- 10%.

PHYSICAL

Environment	IP65 (Dust/Splash Proof) IP68 (Water/ Chemical Resistant)
Operating Temp	-15° to 140°F (-25° to 60° C)
Mounting	3M Adhesive - Clips - Channels
Cut Length	3.93" In (9.98 cm)

QUALITY ASSURANCE

Lumen Maintenance	50,000 Hrs
Warranty	2 Years
CCT Binning	3-Step MacAdam
Certifications	UL, Wildlife Certified (red/yellow IP68)

ELECTRICAL

Voltage	24V
Wire Size	20 AWG. 2 Wire
Lead	Default: 120" Inch IP65: 2" Inch (50.8 mm) Minimum IP65: 3" Inch (76.2 mm) Minimum Quick Connect: 3" - 120" Inch
Jumper	IP65 & IP68: 3" Inch (76.2 mm) Minimum
Dimming	MLV 0-10V S3i Series Controller

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Oct.20.23.08:45

800.595.6302

novaflexled.com