


ORDER GUIDE - DESIGN SERIES STATIC COLOR

NFDS-STC 6.6W | NF-DS-240



PART NUMBER BUILDER:




Notes:

1. All Wet LED products are NOT field trimmable.
2. Output can vary +/- 10%.

ENVIRONMENT AND DIMENSIONS

IN INCHES UNLESS NOTED



| Section | Damp | Wet |
|---------|------------------|------------------|
| A | 0.55" (13.97 mm) | 0.70" (17.78 mm) |
| B | 0.98" (2.49 cm) | 0.98" (2.49 cm) |
| C | 0.32" (8.1 mm) | 0.32" (8.1 mm) |
| D | 0.14" (3.56 mm) | 0.28" (7.1 mm) |

ILLUMINATION DETAILS

| CCT | Lumens/Ft | Efficacy (lm/w) | Power (w/ft) | Max Run |
|--------|-----------|-----------------|--------------|----------|
| Red | 173 | 26 | 6.6 | 13.8' Ft |
| Green | 286 | 43 | | |
| Blue | 64 | 11 | | |
| Yellow | 113 | 17 | | |

PHYSICAL

| | |
|----------------|--|
| Environment | IP65 (Dust/Splash Proof) IP68 (Water/ Chemical Resistant) |
| Operating Temp | -15° to 140°F (-25° to 60° C) |
| Mounting | 3M Adhesive - Clips - Channels |
| Cut Length | 0.98" In (2.49 cm) |

QUALITY ASSURANCE

| | |
|-------------------|--|
| Lumen Maintenance | 50,000 Hrs |
| Warranty | 2 Years |
| CCT Binning | 3-Step MacAdam |
| Certifications | UL, Wildlife Certified (red/yellow IP68) |

ELECTRICAL

| | |
|-----------|--|
| Voltage | 24V |
| Wire Size | 20 AWG. 2 Wire |
| Lead | Default: 120" Inch Damp: 2" Inch (50.8 mm) Min Wet: 3" Inch (76.2 mm) Min Quick Connect: 3" - 120" Inch |
| Jumper | 3" Inch (76.2 mm) Minimum |
| Dimming | MLV 0-10V S3i Series Controller |

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Feb.12.24.10:58

800.595.6302

novaflexled.com