

# CHANNEL - LIGHT LOSS AND TRANSMISSION SS-WHE



## IP RATING

**DRY** Dry **WET** Wet

## BODY COLOR

**SLV** Silver **BLK** Black **WHT** White

## LENS TYPE

**CLR** Clear **SFT** Soft **BLK** Black **SLD** Solid

\*Lead time for this configuration is 7-10 weeks.

## SURFACE

1707		1707-30°		1707-60°		3525		1813	
Light Loss	Light Transmission	Light Transmission		Light Transmission		Light Loss	Light Transmission	Light Loss	Light Transmission
<b>SLV</b> -10%	<b>DRY</b>	<b>DRY</b>		<b>DRY</b>		<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>
<b>BLK</b> * -20%	92%	92%	<b>30° CLR</b>	92%	<b>60° CLR</b>	<b>BLK</b> * -20%	92% TBD <b>CLR</b>	<b>BLK</b> * -20%	92% TBD <b>CLR</b>
<b>WHT</b> * 0%	78%					<b>WHT</b> * 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% TBD <b>SFT</b>
	25%						25% TBD <b>BLK</b>		25% TBD <b>BLK</b>
	50%						50% TBD <b>SLD</b>		50% TBD <b>SLD</b>

## RECESSED

2515		4540		1919U		3030 SQ		3030 CR	
Light Loss	Light Transmission	Light Loss	Light Transmission	Light Loss	Light Transmission	Light Loss	Light Transmission	Light Transmission	
<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b>	<b>DRY</b>	
<b>BLK</b> * -20%	92% TBD <b>CLR</b>	<b>BLK</b> * -20%		<b>BLK</b> * -20%	92% TBD <b>CLR</b>	<b>BLK</b> * -20%	92% <b>CLR</b>	92%	<b>CLR</b>
<b>WHT</b> * 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% <b>SFT</b>	78%	<b>SFT</b>
	25% TBD <b>BLK</b>		25% TBD <b>BLK</b>		25% TBD <b>BLK</b>		25% <b>BLK</b>	25%	<b>BLK</b>
	50% TBD <b>SLD</b>								

## ANGLED

## BENDABLE

3916		1806		3560		2217	
Light Loss	Light Transmission	Light Loss	Light Transmission	Light Loss	Light Transmission	Light Loss	Light Transmission
<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b>	<b>SLV</b> * -10%	<b>DRY</b> <b>WET</b>	<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>
<b>BLK</b> * -20%	92% TBD <b>CLR</b>	<b>BLK</b> * -20%	92% <b>CLR</b>	<b>BLK</b> -20%		<b>BLK</b> * -20%	92% TBD <b>CLR</b>
<b>WHT</b> * 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% <b>SFT</b>	<b>WHT</b> 0%	78% TBD <b>SFT</b>	<b>WHT</b> * 0%	78% TBD <b>SFT</b>
	25% TBD <b>BLK</b>		25% <b>BLK</b>		25% TBD <b>BLK</b>		25% TBD <b>BLK</b>
	50% TBD <b>SLD</b>		50% <b>SLD</b>		50% TBD <b>SLD</b>		

## UNIVERSAL

## MUD-IN

6214	
Light Loss	Light Transmission
<b>SLV</b> -10%	<b>DRY</b> <b>WET</b>
<b>BLK</b> * -20%	92% TBD <b>CLR</b>
<b>WHT</b> * 0%	78% TBD <b>SFT</b>
	25% TBD <b>BLK</b>
	50% TBD <b>SLD</b>

## CHANNELESS

2913	
Light Transmission	
<b>DRY</b> <b>WET</b>	
78% TBD <b>SFT</b>	

## SUSPENDED

3030 RN	
Light Loss	Light Transmission
<b>SLV</b> -10%	<b>DRY</b>
<b>BLK</b> * -20%	
<b>WHT</b> * 0%	78% <b>SFT</b>
	25% <b>BLK</b>

\*Lead time for this configuration is 7-10 weeks

Nova Flex LED LLC retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Jan.23.24.02:38

800.595.6302

novaflexled.com