

COMPATIBILITY - POWER AND CONTROL

SS-WHE



Product Image	Product Code	Dimensions and Description	Compatible
	Series Wattage Voltage Type NF-PS 35W 24V HW 35W Non-DIM Driver (Static)	Output Current: 1.5A Input Voltage: 90 - 246 VAC UL8750, Class 2, Type HL, FCC	
	Series Wattage Voltage Type NF-PS 60W 24V HW 60W Non-DIM Driver (Static)	Output Current: 2.5A Input Voltage: 90 - 246 VAC UL8750, Class 2, Type HL, FCC	
	Series Type Application NF A UNV Universal Amplifier (Dynamic)	Input Voltage: 12 - 36V DC Input Signal: PWM Max Load Current: 20A (5A/4CH) Max Output Power: 240 - 720W	
	Series Type Wattage Voltage NF-PS L3DO 96W 24V 96W Lutron (Dynamic)	Output Current: 4.0A Input Voltage: 120-277VAC UL8750, CSA250.13-14, Class 2	
	Series Type Wattage Voltage NF WC MINI DRGB Mini DRGB Dimmer (Dynamic)	Output: SPI Zones: 1 Dimming Function: 0 - 100% Battery Operated: 3V (CR2032)	
	Series Type Wattage Voltage NF-PS MAXX 30W 24V-0/10V 30W DIM Driver (Dynamic)	Output Current: 1.25A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	
	Series Type Wattage Voltage NF-PS MAXX 288W 24V-0/10V 96W DIM Driver (Dynamic)	Output Current: 0.96A Max Input Voltage: 120-277 VAC UL8750, Class 2	
	Series Type Wattage Type NF S3i WR 1009 S3i Wireless Receiver (Dynamic)	Output Power: 240 - 720w Output Current: 4 CH. 5A/CH Input: 12 - 36V DC Dimming: 0 - 100%	
	Series Series Type Type NF S3i PB RGB/W S3i Push Controller - RGB/W (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 1 Dimming Function: 0 - 100% and RGBW Color Battery Operated: 3V (CR2025)	
	Series Wattage Voltage Type NF S3i PB AS S3i Push Controller - Adjustable (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 1 Dimming Function: 0 - 100% and Kelvin Temp Battery Operated: 3V (CR2025)	
	Series Wattage Voltage Type NF S3i PB D S3i Push Controller - Static DIM (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 1 Dimming Function: 0 - 100% Battery Operated: 3V (CR2025)	

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Jan.23.24.02:38

800.595.6302

novaflexled.com

COMPATIBILITY - POWER AND CONTROL

SS-WHE



Product Image	Product Code	Dimensions and Description	Compatible
	Series: NF Wattage: S3i Voltage: WC Type: RGB/W S3i Handheld Controller - RGB/W (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 6 Dimming Function: 0 - 100% and RGBW Color Battery Operated: 3 AAA	
	Series: NF Type: S3i Wattage: WC Voltage: AS S3i Handheld Controller - Adjustable (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 6 Dimming Function: 0 - 100% and Kelvin Temp Battery Operated: 3 AAA	
	Series: NF Type: S3i Wattage: WC Voltage: D S3i Handheld Controller - Static DIM (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 6 Dimming Function: 0 - 100% Battery Operated: 3 AAA	
	Series: NF Type: S3i Wattage: TP Voltage: RGB S3i Touch Panel - RGB (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 4 Power Consumption: 200 mA Dimming Function: 0 - 100% and RGB Color	
	Series: NF Type: S3i Wattage: TP Voltage: RGB/W S3i Touch Panel - RGB/W (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 3 Power Consumption: 20 mA Dimming Function: 0 - 100% and RGBW Color	
	Series: NF Type: S3i Wattage: TP Voltage: AS S3i Touch Panel - Adjustable (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 3 Power Consumption: 200 mA Dimming Function: 0 - 100% and Kelvin Temp	
	Series: NF Type: S3i Wattage: TP Voltage: D S3i Touch Panel - Static Dim (Dynamic)	Required to Pair: S3i-WR-1009 Zones: 4 Power Consumption: 200 mA Dimming Function: 0 - 100%	
	Series: NF Type: DMX Wattage: 5A Voltage: 4CH Universal DIM Decoder - DMX and/or 0-100 (Dynamic)	Output Current: 5A x 4CH Input Voltage: 12 - 25 VDC UL8750, Class 2, Type HL, FCC	
	Series: NF Wattage: DMX Voltage: PIXEL Type: DECODER DMX to S3i Decoder for Pixel (Dynamic)	Output Signal: SPI Decoding Channels: 512 Input Voltage: 5 - 24 VDC UR and UL recognized component	
	Series: NF-PS Type: UNV Wattage: 30W Voltage: 24V Universal DIM Power 30 Watts (Dynamic)	Output Current: 0.5 A Input Voltage: 120 - 277 VAC UL8750, Class 2, Type HL, FCC	
	Series: NF-PS Type: UNV Wattage: 60W Voltage: 24V Universal DIM Power 60 Watts (Dynamic)	Output Current: 2.5A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Jan.23.24.02:38









800.595.6302

novaflexled.com

COMPATIBILITY - POWER AND CONTROL

SS-WHE



Product Image	Product Code				Dimensions and Description	Compatible
   	Series	Type	Wattage	Voltage	Output Current: 3.33 A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	
	NF-PS	UNV	80W	24V		
	Universal DIM Power 80 Watts (Dynamic)					
	Series	Type	Wattage	Voltage	Output Current: 4A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	
	NF-PS	UNV	96W	24V		
	Universal DIM Power 96 Watts (Dynamic)					
	Series	Type	Wattage	Voltage	Output Current: 3x4A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	
	NF-PS	UNV	288W	24V		
	Universal DIM Power 288 Watts (Dynamic)					
	Series	Type	Wattage	Voltage	Output Current: 4x4A Input Voltage: 100-277 VAC UL8750, Class 2, Type HL, FCC	
	NF-PS	UNV	384W	24V		
	Universal Non-DIM Power 384 Watts (Dynamic)					

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

PROJECT

FIXTURE

PHASE

DATE

Rev: Jan.23.24.02:38

800.595.6302

novaflexled.com