
ORDER GUIDE - MINI NEON 2.0 STATIC COLOR

NF-NEON STC 3.7W



PART NUMBER BUILDER:



- 1. IP67 finished with our in-house custom injection molding
- 2. Refined finish IP68 available upon request with 7-10 week lead time
- 3. Salt and UV resistant (Anti-yellow), IK08 protection

DIMENSIONS





PHYSICAL

Environment	IP67
Ambient Temp	-40° to 131°F (-40° to 55°C)
Cut Length	3.28" Inches (8.33 cm)
Min. Bend Diameter	4.72" Inches (11.98 cm)
Bend Direction	Side Bend
Max Run	26.24' Feet (7.99 m)
Lead Wire	11.8" Inches (29.97 cm)
Jumper	11.8" Inches (29.97 cm)

NOVA*FLEX

ILLUMINATION DETAILS; RED





AVERAGE BEAM ANGLE (50%):113.8 DEG

Color	Peak Wave Length (nm)	FWHM (nm)	Output L/Ft	Efficacy L/W
Green	517.0	26.0	107	29.2
Blue	463.7	20.6	21	5.7

Lumen values can vary +/- 10%

ELECTRICAL

Voltage	24V
Wattage	3.7 W/Ft
Wire Size	18 AWG, 2-wires (RED = 24V, BLACK = ground)
Dimming	PWM / PFM IEEE PAR1789 No Effect Level Green for Flicker when used with Nova Flex drivers and Dimming modules.
Dimming Control	0-10V MLV / ELV DALI DMX

QUALITY ASSURANCE

Lumen Maintenance	50,000 Hrs
Warranty	7 years
Certifications	cULus listed

Nova Flex retains the right to modify the design of our products at any time as part of the company's continual product improvement program

DATE PROJECT FIXTURE PHASE

800.595.6302 novaflexled.com